

GLOSS WHITE



TYPE 11 COMPACT PANEL RADIATOR DATA SHEET

MATT ANTHRACITE & MATT BLACK



Height H		Width W		Colour	Code	Heat Output $\Delta T50^{\circ}C$		Heat Output $\Delta T60^{\circ}C$		Water Content / Litres	Weight / Kg	For full pallet quantities
mm.	mm.	Watts	BTU			Watts	BTU	Pcs per Pallet				
300	400	RAL9016 Gloss White	25.0010	194	662	245	837	0.68	3.91	40		
	500	RAL9016 Gloss White	25.0011	243	828	307	1047	0.85	4.64	40		
	600	RAL9016 Gloss White	25.0012	291	993	368	1255	1.02	5.38	40		
	800	RAL9016 Gloss White	25.0013	388	1324	490	1674	1.36	6.93	40		
	1000	RAL9016 Gloss White	25.0014	485	1655	613	2092	1.70	8.41	40		
	1200	RAL9016 Gloss White	25.0015	582	1986	736	2510	2.04	9.89	40		
	1400	RAL9016 Gloss White	25.0016	679	2317	858	2929	2.38	11.44	40		
	1600	RAL9016 Gloss White	25.0017	776	2648	981	3347	2.72	12.92	24		
	2000	RAL9016 Gloss White	25.0018	970	3310	1226	4184	3.40	16.05	24		
400	400	RAL9016 Gloss White	25.0019	255	871	322	1101	0.84	5.03	40		
	500	RAL9016 Gloss White	25.0020	319	1089	403	1376	1.05	6.02	40		
	600	RAL9016 Gloss White	25.0021	383	1307	484	1652	1.26	7.00	40		
	700	RAL9016 Gloss White	25.0022	447	1525	565	1928	1.50	7.98	40		
	800	RAL9016 Gloss White	25.0023	511	1743	646	2203	1.68	9.03	40		
	900	RAL9016 Gloss White	25.0024	575	1960	727	2477	1.90	10.02	40		
	1000	RAL9016 Gloss White	25.0025	638	2178	806	2753	2.10	11.00	40		
	1100	RAL9016 Gloss White	25.0026	702	2396	887	3029	2.30	11.97	40		
	1200	RAL9016 Gloss White	25.0027	766	2614	968	3304	2.52	12.95	40		
	1400	RAL9016 Gloss White	25.0028	894	3050	1130	3855	2.94	15.00	40		
	1600	RAL9016 Gloss White	25.0029	1021	3485	1291	4405	3.36	16.96	24		
	1800	RAL9016 Gloss White	25.0030	1149	3921	1452	4956	3.80	18.43	24		
	2000	RAL9016 Gloss White	25.0031	1277	4357	1614	5507	4.20	21.11	24		
500	400	RAL9016 Gloss White	25.0032	314	1072	397	1355	1.04	6.18	40		
	500	RAL9016 Gloss White	25.0033	393	1340	497	1694	1.30	7.41	40		
	600	RAL9016 Gloss White	25.0034	471	1608	595	2033	1.56	8.64	40		
	700	RAL9016 Gloss White	25.0035	550	1876	695	2371	1.80	9.87	40		
	800	RAL9016 Gloss White	25.0036	628	2144	794	2710	2.08	11.17	40		
	900	RAL9016 Gloss White	25.0037	707	2412	894	3049	2.30	12.40	40		
	1000	RAL9016 Gloss White	25.0038	785	2680	992	3388	2.60	13.64	40		
	1100	RAL9016 Gloss White	25.0039	864	2948	1092	3726	2.90	14.87	40		
	1200	RAL9016 Gloss White	25.0040	942	3216	1191	4065	3.12	16.10	40		
	1300	RAL9016 Gloss White	25.0041	1021	3484	1291	4404	3.40	17.40	40		
	1400	RAL9016 Gloss White	25.0042	1100	3752	1390	4743	3.64	18.63	40		
	1500	RAL9016 Gloss White	25.0043	1175	4009	1485	5067	3.90	19.87	40		
	1600	RAL9016 Gloss White	25.0044	1257	4288	1589	5420	4.16	21.10	24		
	1800	RAL9016 Gloss White	25.0045	1414	4824	1787	6098	4.70	23.83	24		
	2000	RAL9016 Gloss White	25.0046	1571	5360	1986	6775	5.20	26.29	24		

Height H mm.	Width W mm.	Colour	Code	Heat Output $\Delta T50^{\circ}\text{C}$		Heat Output $\Delta T60^{\circ}\text{C}$		Water Content / Litres	Weight / Kg	For full pallet quantities
				Watts	BTU	Watts	BTU			Pcs per Pallet
600	400	RAL9016 Gloss White	25.0047	370	1263	468	1596	1.24	7.34	20
	500	RAL9016 Gloss White	25.0048	463	1578	585	1995	1.55	8.82	20
	600	RAL9016 Gloss White	25.0049	555	1894	702	2394	1.86	10.30	20
	700	RAL9016 Gloss White	25.0050	648	2209	819	2792	2.20	11.79	20
	800	RAL9016 Gloss White	25.0051	740	2525	935	3192	2.48	13.34	20
	900	RAL9016 Gloss White	25.0052	833	2841	1053	3591	2.80	14.82	20
	1000	RAL9016 Gloss White	25.0053	925	3156	1169	3989	3.10	16.30	20
	1100	RAL9016 Gloss White	25.0054	1018	3472	1287	4389	3.40	17.78	20
	1200	RAL9016 Gloss White	25.0055	1110	3788	1403	4788	3.72	19.27	20
	1300	RAL9016 Gloss White	25.0056	1195	4078	1510	5155	4.00	20.82	20
	1400	RAL9016 Gloss White	25.0057	1295	4419	1637	5586	4.34	22.30	20
	1500	RAL9016 Gloss White	25.0058	1385	4726	1751	5974	4.70	23.78	20
	1600	RAL9016 Gloss White	25.0059	1480	5050	1871	6383	4.96	25.26	12
	1800	RAL9016 Gloss White	25.0060	1665	5682	2105	7182	5.60	28.55	12
2000	RAL9016 Gloss White	25.0061	1850	6313	2338	7980	6.20	31.51	12	
600	400	Matt Anthracite	25.0062	370	1263	468	1596	1.24	7.34	20
	600	Matt Anthracite	25.0063	555	1894	702	2394	1.86	10.30	20
	800	Matt Anthracite	25.0064	740	2525	935	3192	2.48	13.34	20
	1000	Matt Anthracite	25.0065	925	3156	1169	3989	3.10	16.30	20
	1200	Matt Anthracite	25.0066	1110	3788	1403	4788	3.72	19.27	20
	1400	Matt Anthracite	25.0067	1295	4419	1637	5586	4.34	22.30	20
	1600	Matt Anthracite	25.0068	1480	5050	1871	6383	4.96	25.26	12
	1800	Matt Anthracite	25.0069	1665	5682	2105	7182	5.60	28.55	12
600	400	Matt Black	25.0070	370	1263	468	1596	1.24	7.34	20
	600	Matt Black	25.0071	555	1894	702	2394	1.86	10.30	20
	800	Matt Black	25.0072	740	2525	935	3192	2.48	13.34	20
	1000	Matt Black	25.0073	925	3156	1169	3989	3.10	16.30	20
	1200	Matt Black	25.0074	1110	3788	1403	4788	3.72	19.27	20
	1400	Matt Black	25.0075	1295	4419	1637	5586	4.34	22.30	20
	1600	Matt Black	25.0076	1480	5050	1871	6383	4.96	25.26	12
	1800	Matt Black	25.0077	1665	5682	2105	7182	5.60	28.55	12

Heat Output $\Delta T50^{\circ}\text{C}$ means boiler flow temperature of 70°C and a room temperature of 20°C .

Heat Output $\Delta T60^{\circ}\text{C}$ means boiler flow temperature of 80°C and a room temperature of 20°C .

Type 11 - Technical Drawing

Height H (mm.)	Horizontal Tappings L (mm.)	Vertical Tappings B (mm.)	Radiator Depth C (mm.)	Tappings from Wall D (mm.)
300	W	245	50	38 / 50
400	W	345	50	38 / 50
500	W	445	50	38 / 50
600	W	545	50	38 / 50

* Radiators have 4 tappings in total.

Wall Brackets

Radiator Height (mm.)	Bracket Length F (mm.)	Bracket Drilling Centre E (mm.)	Wall Bracket Code for 2 pcs	Wall Bracket Code for 3 pcs	Wall Bracket Quantity	
					2 pieces	3 pieces
300	108	-	25.9001	25.9005	Radiator Width 400 to 1600mm	Radiator Width 1800 to 2000mm
400	210	99	25.9002	25.9006		
500	309	198	25.9003	25.9007		
600	407	296	25.9004	25.9008		

*All wall brackets for all colour radiators come in galvanised colour (nickel).
 All radiators come with wall fixings and wall brackets. Wall Bracket codes are stated above for spare part requests.

Bracket Positioning

Radiator Width W (mm.)	Type 11 / Type 21 / Type 22							
	a (mm.)	b (mm.)	c (mm.)		d (mm.)		e (mm.)	f (mm.)
			Type 11	Type 21 / 22	Type 11	Type 21 / 22		
400 - 1600	W - 266.6	-	117	133.3	117	133.3	-	-
1800 - 2000	(W / 2) - 133.3	(W / 2) - 133.3	133.3		133.3		W / 2	W / 2

Our compact panel radiators are packed in heavy duty, protective packaging. Side cartons, bubble wrap, plastic corner protection and shrink wrap will protect these radiators to their destination.

- Branded cardboard sides with reinforced plastic protection corner pads
- Plastic bracket protectors
- Entirely polythene sealed
- Side ID label
- Bubble Wrap
- Instruction manual
- Front and side A4 identification label